


125.3FC-SS




FOR FASTENING FIBRE CEMENT CORRUGATED SHEETS (55MM-85MM THICKNESS) TO PURLINS OF 1.5MM-6MM THICKNESS. SUPPLIED WITH BAZ WASHER.

PROPERTIES



| | |
|------------------------------|--------------------------------|
| MATERIAL | STAINLESS STEEL A2 - 304 GRADE |
| COATING | 500 HRS (SILVER) |
| HEAD TYPE | HEX |
| DRILL POINT | 3 PT |
| EFFECTIVE THREAD LENGTH | 47.00 |
| RECOMMENDED DRILL BIT/SOCKET | SOCKET-HEX-5/16"RING |
| RECOMMENDED DRILL SPEED | 1500 - 2500 RPM |



PERFORMANCE

PULL OUT



| | | | | | |
|----------------------|------|-------|-------|-----|-----|
| STEEL THICKNESS (MM) | 2.00 | 4.00 | 6.00 | N/A | N/A |
| VALUE (kN) | 6.50 | 12.97 | 15.00 | | |

Grade of material: S275 Steel

PULL OVER



| | | | | |
|----------------------|------------|------|------------|------|
| WASHER | 16MM x 2MM | | 19MM x 2MM | |
| SHEET THICKNESS (MM) | 0.50 | 0.70 | 0.50 | 0.70 |
| VALUE (kN) | | | | |

SHEAR



| | |
|------------|-------|
| VALUE (kN) | 13.94 |
|------------|-------|

TENSILE



| | |
|------------|-------|
| VALUE (kN) | 16.08 |
|------------|-------|

DIMENSIONS

| | |
|--------|--------|
| A (MM) | 8.71 |
| B (MM) | 125.00 |
| C (MM) | 52.00 |
| D (MM) | 6.35 |
| E (MM) | 8.00 |
| F (MM) | 5.30 |
| G (MM) | 12.60 |