



25.1 SSLPW(A4)

FOR STITCHING MAX 2 X 1.25MM SHEETS

PROPERTIES




| | |
|------------------------------|--------------------------------|
| MATERIAL | STAINLESS STEEL A4 - 316 GRADE |
| COATING | BRIGHT ZINC PLATING |
| HEAD TYPE | LOW PROFILE |
| DRILL POINT | 1 PT |
| EFFECTIVE THREAD LENGTH | 17.00 |
| RECOMMENDED DRILL BIT/SOCKET | BIT-T25 |
| RECOMMENDED DRILL SPEED | 1500 - 2500 RPM |



PERFORMANCE


PULL OUT



| | | | | | |
|----------------------|----------|-----|-----|-----|-----|
| STEEL THICKNESS (MM) | 2 x 0.70 | N/A | N/A | N/A | N/A |
| VALUE (kN) | 2.90 | | | | |


Grade of material: Plastisol Sheet

PULL OVER




| | | | | |
|----------------------|------------|------|------------|------|
| WASHER | 16MM x 2MM | | 19MM x 2MM | |
| SHEET THICKNESS (MM) | 0.50 | 0.70 | 0.50 | 0.70 |
| VALUE (kN) | | | | |

SHEAR



| | |
|------------|------|
| VALUE (kN) | 9.52 |
|------------|------|

TENSILE



| | |
|------------|------|
| VALUE (kN) | 7.22 |
|------------|------|

DIMENSIONS

| | |
|--------|-------|
| A (MM) | 14.50 |
| B (MM) | 25.00 |
| C (MM) | 19.50 |
| D (MM) | 6.30 |
| E (MM) | 5.50 |
| F (MM) | 4.00 |
| G (MM) | N/A |