



# 38.2SS(A4)

FOR FASTENING SHEET TO PURLINS OF 1.2MM-3.5MM THICKNESS

## PROPERTIES




MATERIAL	STAINLESS STEEL A4 - 316 GRADE
COATING	500 HRS (SILVER)
HEAD TYPE	HEX
DRILL POINT	2 PT
EFFECTIVE THREAD LENGTH	29.00
RECOMMENDED DRILL BIT/SOCKET	SOCKET-HEX-5/16"RING
RECOMMENDED DRILL SPEED	1500 - 2500 RPM



## PERFORMANCE

### PULL OUT



STEEL THICKNESS (MM)	1.20	1.60	2.00	2.50	3.00
VALUE (kN)	2.76	4.04	5.62	7.70	7.80


Grade of material: S450 Steel

### PULL OVER




WASHER	16MM x 2MM		19MM x 2MM	
SHEET THICKNESS (MM)	0.50	0.70	0.50	0.70
VALUE (kN)				

### SHEAR



VALUE (kN)	8.56
------------	------

### TENSILE



VALUE (kN)	8.78
------------	------

## DIMENSIONS

A (MM)	8.71
B (MM)	38.00
C (MM)	32.10
D (MM)	5.50
E (MM)	5.90
F (MM)	4.50
G (MM)	12.60