


# HT100.2




FOR FASTENING COMPOSITE PANELS (40MM-75MM THICKNESS) TO PURLINS OF 1.2MM-3.5MM THICKNESS

## PROPERTIES




MATERIAL	CARBON STEEL
COATING	500 HRS (SILVER)
HEAD TYPE	HEX
DRILL POINT	2 PT
EFFECTIVE THREAD LENGTH	55.00
RECOMMENDED DRILL BIT/SOCKET	SOCKET-HEX-5/16" MAG
RECOMMENDED DRILL SPEED	1500 - 2500 RPM



## PERFORMANCE

### PULL OUT



STEEL THICKNESS (MM)	1.20	1.60	2.00	2.50	3.00
VALUE (kN)	2.62	4.10	5.38	7.16	7.74


Grade of material: S450 Steel

### PULL OVER




WASHER	16MM x 2MM		19MM x 2MM	
SHEET THICKNESS (MM)	0.50	0.70	0.50	0.70
VALUE (kN)	3.92	5.61	4.01	5.80

### SHEAR




VALUE (kN)	7.30
------------	------

### TENSILE



VALUE (kN)	16.00
------------	-------

## DIMENSIONS



A (MM)	8.64
B (MM)	100.00
C (MM)	60.00
D (MM)	5.50
E (MM)	7.00
F (MM)	4.52
G (MM)	12.25