

# HT130.5LP




FOR FASTENING COMPOSITE PANELS (50MM-100MM THICKNESS) TO PURLINS OF 4MM-12.5MM THICKNESS

## PROPERTIES



MATERIAL	CARBON STEEL
COATING	BRIGHT ZINC PLATING
HEAD TYPE	LOW PROFILE
DRILL POINT	5 PT
EFFECTIVE THREAD LENGTH	71.00
RECOMMENDED DRILL BIT/SOCKET	BIT-T25
RECOMMENDED DRILL SPEED	1500 - 2500 RPM



## PERFORMANCE

### PULL OUT



STEEL THICKNESS (MM)	4.00	6.00	8.00	10.00	12.00
VALUE (kN)	10.00	12.68	12.68	12.68	12.68

Grade of material: S275 Steel

### PULL OVER



WASHER	16MM x 2MM		19MM x 2MM	
SHEET THICKNESS (MM)	0.50	0.70	0.50	0.70
VALUE (kN)				

### SHEAR




VALUE (kN)	8.53
------------	------

### TENSILE



VALUE (kN)	12.68
------------	-------

## DIMENSIONS



A (MM)	14.50
B (MM)	130.00
C (MM)	75.00
D (MM)	5.50
E (MM)	15.00
F (MM)	5.00
G (MM)	N/A